



## EU DECLARATION OF CONFORMITY



**Copreci S.Coop.**  
**Araba Ibilbidea, 3**  
**E-20550 Aretxabaleta-GIPUZKOA (Spain)**  
**Tlfn: + 34 943034499**

Declare under our sole responsibility that the product:

| Model          | PIN<br>AENOR | Description  |
|----------------|--------------|--|
| T15<br>T15 EID | 99CT952      | Manually operated valve with a flame supervision device for gas burning appliances |

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EN 1106: Manually operated taps for gas burning appliances
- EN 125: 2010 + A1:2016: Flame supervision devices for gas burning appliances. Thermo-electric flame supervision devices
- EN 13611:2016: Safety and control devices for burners and appliances burning gaseous and/or liquid fuels. General requirements

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/001873 certificate, on 22/9/2003 and valid until 22/09/2018.

This certificate is valid from 04/21/2018

Aitziber Kortabarria  
 Copreci, S. Coop.  
 Laboratory Manager

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical information for the installer

| INSTRUCTIONS                    |   |
|---------------------------------|---|
| MODEL                           | T15   |
| GROUP                           | 1   |
| PURPOSE                         | Heaters   |
| CHARACTERISTICS                 | Number of ways: 1<br>Maximum pressure: 2000 mB<br>Reference flow: 0.450 m <sup>3</sup> /h air with 1 mbar. pressure drop<br>Nominal diameter: <6<br>T <sup>a</sup> max.: 80°C<br>T <sup>a</sup> min.: 0°C |
| NUMBER OF MECHANICAL CYCLES     | 10000 cycles  |
| MOUNTING POSITION               | multiposition   |
| CONNECTIONS                     | Depending on the manufacturer's requirements.   |
| TORQUE OF FITTING OUTLET (max)  | 8 Nm (bicone)<br>15 Nm (flared pipe)  |
| TORQUE OF FITTING INLET (max)   | 8 Nm (bicone)<br>15 Nm (flared pipe)  |
| PUSHING FORCE (max)             | 30 N  |
| TURNING TORQUE OF SPINDLE (max) | 0.4Nm   |
| PULL IN CURRENT                 | Different options: <ul style="list-style-type: none"> <li>• 240 ÷ 110 mA</li> <li>• 200 ÷ 80 mA</li> <li>• 180 ÷ 60 mA</li> </ul>   |
| OPENING TIME                    | 2 seg (thermocouple optimal position)   |
| CLOSING TIME                    | < 60seg   |
| PRESSURES RANGE                 | 8 - 2000 mbar   |
| GASES OF USE                    | 2nd y 3th families  |

2. Instruction manual for use and maintenance intended for the user.

- Component does not require any maintenance. Washing the thermostat with soapy water or other products may involve deterioration.
- Do not pour liquids in the component.
- The appliance can only be switched on in the user's presence.
- The component must not be manipulated or repaired in any way
- In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.
- The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance
- The installer must check the suitability of the component functions for the intended use

