



## Gas Components for Catering Equipments

Component	Type	Power kW (l/h)			Flow l/hour Air 20 mbar	Dimensions and others
		LPG G-30/G-31 30/37 mbar	Natural Gas G-20 20 mbar	Town Gas G-110 10 mbar		
Safety valve	CAL - 3200	46 kW (1.335)	22 kW (2.095)	7,6 kW (1.720)	1.560	According to customer requirements
Safety valve	CPMM - 18700	23 kW (665)	11 kW (1.050)	3,8 kW (1.220)	780	
Safety valve	CAL - 5200	13 kW (390)	6,5 kW (620)	2,3 kW (510)	460	
Safety valve	ACAL - 10200	13 kW (390)	6,5 kW (620)	2,3 kW (510)	460	
Safety valve	CAL - 20700	10,8 kW (250)	5 kW (480)	1,7 kW (390)	355	
Milivolt valve	VmV - 23500	52 kW (1.500)	25 kW (2.380)	8,7 kW (1.960)	1.770	
Thermostat	MT / MTZ - 7200	17 kW (485)	8 kW (760)	2,8 kW (625)	570	
Thermostat	MTZ - 22300	11,5 kW (350)	5,5 kW (525)	1,9 kW (430)	390	
Safety push valve	T-10 / T-15 / T-25	17 / 25 / 52 kW	8 / 12 / 25 kW	2,8 / 4 / 8,7 kW	570 / 850 / 1.770	
Pilot	P - 23300	With 1, 2 and 3 flames and with or without spark plug - 23300				

1 kW= 3.413 Btu/h=860 Kcal/h