



EU DECLARATION OF CONFORMITY

COPRECI

Copreci de Mexico
Calle uno #736 Colonia Industrial 44940
Guadalajara, Jalisco, Mexico.
Tlfn: + 52 33 38811170

Declare under our sole responsibility that the product:

Model	PIN	Description
490	CE	Manually operated valve for gas burning appliances
491	688298	
492		

To which this declaration relates is in compliance with the regulation EU 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- BS EN 1106: Manually operated taps for gas burning appliances

The notified body BSI (NB number 2797, BSI Group the Netherlands B.V. Address: Say Building, John M. Keynesplein 9, 1066 EP Amsterdam | P.O. Box 74103, 1070 BC Amsterdam The Netherlands) performed the evaluation of the conformity procedure with the type based on the product quality assurance.

This certificate is valid from 02/ 15/ 2022

Name: Araceli Itzell Muñoz Cortes

Title/Position: Quality System and Service

Place & date of issue: Guadalajara, Jalisco, may 17th 2024

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical information for the installer

INSTRUCTIONS	
MODEL	490, 491, 492
GROUP	1
PURPOSE	Surface burner
CHARACTERISTICS	Maximum pressure: 65 mB Reference flow: 0.082 m ³ /h air with 1 mbar. pressure drop Nominal orifice diameter: <6 T ^a max.: 150°C brass body, 110°C aluminium body T ^a min.: 0°C
NUMBER OF MECHANICAL CYCLES	40000 cycles
MOUNTING POSITION	multiposition
CONNECTIONS	Depending on the manufacturer's requirement
TORQUE OF FITTING OUTLET (max)	8 Nm (bicone) 10 Nm (flared pipe)
TORQUE OF FITTING INLET (max)	3 Nm
PUSHING FORCE (max)	30 N
TURNING TORQUE OF SPINDLE (max)	0.2Nm
GASES OF USE	1 st , 2nd, 3rd families

2. Instruction manual for use and maintenance intended for the user.

- *Component does not require any maintenance. Washing the thermostat with soapywater or other products may involve deterioration.*
- *Do not pour liquids in the component.*
- *The appliance can only be switched on in the user's presence.*
- *The component must not be manipulated or repaired in any way*
- *In case of malfunction, the manufacturer of the appliance and its specialized technicalservice carries out the replacement of the component.*
- *The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance*
- *The installer must check the suitability of the component functions for the intended use*

3. ANNEX EU DECLARATION OF CONFORMITY

- *Description: Manually operated valve for gas burning appliances/ Model 490, 491, 492.*
- *Manufacturer: COPRECI DE MÉXICO SA DE CV, #736 Streat 1, Guadalajara Jalisco 44940 México.*
- *This declaration of conformity is issued under the sole responsibility by COPRECI DE MÉXICO SA DE CV.*
- *Description of the appliance or the fitting:*

INSTRUCTIONS	
MODEL	490, 491, 492
GROUP	1
PURPOSE	Surface burner
CHARACTERISTICS	Maximum pressure: 65 mB Reference flow: 0.082 m ³ /h air with 1 mbar. pressure drop Nominal orifice diameter: <6 T ^a max.: 150°C brass body, 110°C aluminium body T ^a min.: 0°C

- *To which this declaration relates is in compliance with the regulation EU 2016/426 of the European parliament on appliances burning gaseous fuels.*
- *INSTALLATION: The attached gas valves must be installed only by qualified personnel and with the required connections and seals. Each assembly must be tested for leakage.*
- *ADJUSTMENTS: The gas valves do not require any adjustment for their installation.*
- *OPERATION: To open the gas valves push the stem and turn it counter clockwise.*
- *MAINTENANCE: These gas valves do not require any maintenance and should not be Unassembled. If damage or leakage is detected the valve must be replaced*