

**EU DECLARATION OF CONFORMITY**

***Copreci S.Coop.  
Araba Ibilbidea, 3  
E-20550 Aretxabaleta-GIPUZKOA (Spain)  
Tlfn: + 34 943034499***

Declare under our sole responsibility that the product:

Model	PIN AENOR	Description
CAL 3200 CAL 3201	99CT959	Manually operated multifunctional valve with a flame supervision device for gas burning appliances

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EN 1106: Manually operated taps for gas burning appliances
- EN 126: 2012: Multifunctional controls for gas burning appliances
- EN 125: 2010 + A1:2016: Flame supervision devices for gas burning appliances. Thermo-electric flame supervision devices
- EN 13611:2016: Safety and control devices for burners and appliances burning gaseous and/or liquid fuels. General requirements
- ROHS Directive 2011/65/EU and amendment 2015/863/EU

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/002173 certificate, on 2021/10/13.

This certificate is valid from 22/08/2023

**Iñigo Peñagarikano**  
Copreci, S. Coop.  
Laboratory Manager

# Instructions for installation of the product subject to this declaration:

"Consult the instructions before using this device. Installation must meet the regulations in force"

## 1. Technical information for the installer

INSTRUCTIONS	
MODEL	CAL 3200
GROUP	1
PURPOSE	Industrial freestanding
CHARACTERISTICS	Number of ways: 1 Maximum pressure: 50 mB Reference flow: 1.5 m <sup>3</sup> /h air with 1 mbar. pressure drop Nominal diameter: <10 T <sub>a</sub> max.: 120°C T <sub>a</sub> min.: 0°C
NUMBER OF MECHANICAL CYCLES	40000 cycles
MOUNTING POSITION	Multi positional
CONNECTIONS	Depending on the oven manufacturer's requirements.
TORQUE OF FITTING OUTLET (max)	8 Nm (bicone) 15 Nm (flared pipe)
TORQUE OF FITTING INLET (max)	3 Nm (bracket) 8 Nm (bicone) 15 Nm (flared pipe)
PUSHING FORCE (max)	30 N
TURNING TORQUE OF SPINDLE (max)	0.2 Nm
PULL IN CURRENT	Different options: <ul style="list-style-type: none"> <li>• 110 ÷ 20 mA</li> <li>• 90 ÷ 10 mA</li> </ul>
OPENING TIME	2 seg (thermocouple optimal position)
CLOSING TIME	< 60seg
PRESSURES RANGE	8 - 50 mbar
GASES OF USE	1st, 2nd y 3th families

## 2. Instruction manual for use and maintenance intended for the user.

- Component does not require any maintenance. Washing the thermostat with soapy water or other products may involve deterioration.
- Do not pour liquids in the component.
- The appliance can only be switched on in the user's presence.
- The component must not be manipulated or repaired in any way
- In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.
- The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance
- The installer must check the suitability of the component functions for the intended use