



EU DECLARATION OF CONFORMITY



Copreci S.Coop.
Araba Ibilbidea, 3
E-20550 Aretxabaleta-GIPUZKOA (Spain)
Tlfn: + 34 943034499

Declare under our sole responsibility that the product:

| Model | PIN AENOR | Description |
|------------|--------------|--|
| CPMM 17700 | 99CT949 | Manually operated multifunctional valve with a flame supervision device for gas burning appliances |

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EN 1106: Manually operated taps for gas burning appliances
- EN 126: 2012: Multifunctional controls for gas burning appliances
- EN 125: 2010 + A1:2016: Flame supervision devices for gas burning appliances. Thermo-electric flame supervision devices
- EN 13611:2016: Safety and control devices for burners and appliances burning gaseous and/or liquid fuels. General requirements

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/002180 certificate, on 2021/10/13.

This certificate is valid from 14/11/2019

Iñigo Peñagarikano
 Copreci, S. Coop.
 Laboratory Manager

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical information for the installer

| INSTRUCTIONS | |
|---------------------------------|--|
| MODEL | CPMM 17700 |
| GROUP | 1 |
| PURPOSE | heaters |
| CHARACTERISTICS | Number of ways: 3 Maximum pressure: 50 mB Reference flow: 0.450 m ³ /h air with 1 mbar. pressure drop Nominal diameter: <10 T ^a max.: 80°C T ^a min.: 0°C |
| NUMBER OF MECHANICAL CYCLES | 10000 cycles |
| MOUNTING POSITION | multiposition |
| CONNECTIONS | Depending on the client requirements. |
| TORQUE OF FITTING OUTLET (max) | 8 Nm (bicone) 15 Nm (flared pipe) |
| TORQUE OF FITTING INLET (max) | 8 Nm (bicone) 15 Nm (flared pipe) |
| PUSHING FORCE (max) | 30 N |
| TURNING TORQUE OF SPINDLE (max) | 0.4Nm |
| PULL IN CURRENT | 200 ÷ 80 mA |
| OPENING TIME | 2 seg (thermocouple optimal position) |
| CLOSING TIME | < 60seg |
| PRESSURES RANGE | 8 - 50 mbar |
| GASES OF USE | 1st, 2nd y 3th families |

2. Instruction manual for use and maintenance intended for the user.

- Component does not require any maintenance. Washing the thermostat with soapy water or other products may involve deterioration.
- Do not pour liquids in the component.
- The appliance can only be switched on in the user's presence.
- The component must not be manipulated or repaired in any way
- In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.
- The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance
- The installer must check the suitability of the component functions for the intended use