



## EU DECLARATION OF CONFORMITY



**Copreci S.Coop.**  
**Araba Ibilbidea, 3**  
**E-20550 Aretxabaleta-GIPUZKOA (Spain)**  
**Tlfn: + 34 943034499**

Declare under our sole responsibility that the product:

| Model    | PIN AENOR | Description   |
|----------|-----------|---|
| MT 9400  | 99CT960   | Manually operated multifunctional valve with a mechanical thermostat for gas burning appliances |
| MTG 9400 |           |   |

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EN 1106: Manually operated taps for gas burning appliances
- EN 126: 2012: Multifunctional controls for gas burning appliances
- EN-257:2010: Mechanical thermostat for gas burning appliances
- EN 13611:2016: Safety and control devices for burners and appliances burning gaseous and/or liquid fuels. General requirements

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/002178 certificate, on 2021/10/13.

This certificate is valid from 14/11/2019

Iñigo Peñagarikano  
 Copreci, S. Coop.  
 Laboratory Manager

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical information for the installer

| INSTRUCTIONS                              |   |
|---|---|
| MODEL                                     | MT, MTG, 9400   |
| GROUP                                     | 1   |
| PURPOSE                                   | Gas ovens<br>For gases of the 1st, 2nd and 3rd families<br>and up to 100 mbar of inlet pressure.  |
| CHARACTERISTICS                           | Reference flow: 0.390 m <sup>3</sup> /h air with 1<br>mbar. pressure drop<br>Nominal diameter: DN 6<br>T <sup>a</sup> max.: 150°C<br>T <sup>a</sup> min.: 0°C |
| NUMBER OF MECHANICAL CYCLES               | 10000 cycles  |
| MOUNTING POSITION                         | Multi positional  |
| CONNECTIONS                               | Depending on the oven manufacturer's<br>requirements.   |
| TORQUE OF FITTING OUTLET (max)            | 8 Nm (bicone)<br>15 Nm (flared pipe)  |
| TORQUE OF FITTING INLET (max)             | 3 Nm  |
| PUSHING FORCE (max)                       | 30 N  |
| TURNING TORQUE OF SPINDLE (max)           | 0.5Nm   |
| GASES OF USE                              | 1st, 2nd y 3th families   |
| CONVERSION TO OTHER GAS FAMILIES          | By-Pass   |
| ADJUSTMENTS, FLOWS, THERMOSTAT DRIFT, ... | Depending on the oven manufacturer's<br>requirements.   |

2. Instruction manual for use and maintenance intended for the user.

- Component does not require any maintenance. Washing the thermostat with soapy water or other products may involve deterioration.
- Do not pour liquids in the component.
- The appliance can only be switched on in the user's presence.
- The component must not be manipulated or repaired in any way
- In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.
- The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance
- The installer must check the suitability of the component functions for the intended use