



## EU DECLARATION OF CONFORMITY



**Copreci S.Coop.**  
**Araba Ibilbidea, 3**  
**E-20550 Aretxabaleta-GIPUZKOA (Spain)**  
**Tlfn: + 34 943034499**

Declare under our sole responsibility that the product:

Model	PIN AENOR	Description
SOV MODEL D (DUAL) SOV MODEL S (SINGLE)	99DP1037	Mechanically operated shut off valve for gas burning appliances

To which this declaration relates is in compliance with the regulation UE 2016/426 of the European parliament on appliances burning gaseous fuels

And comply with the standards listed below

- EU/2016/426 A III B (09.03.2016)
- EN 1106:2022
- EN 13611:2022
- ROHS Directive 2011/65/EU and amendment 2015/863/EU

The notified body AENOR (0099) (C/Génova, 6, 28004 Madrid-España) performed the evaluation of the conformity procedure with the type based on the product quality assurance in accordance with the provisions of module E and issued the A01/002180 certificate, on 2021/10/13.

This certificate is valid from 2024.02.15

Iñigo Peñagarikano  
Copreci, S. Coop.  
Laboratory Manager

Instructions for installation of the product subject to this declaration:

“Consult the instructions before using this device. Installation must meet the regulations in force”

1. Technical instructions for the installer.

<b>INSTRUCTIONS SOV</b>	
<b>MODEL</b>	<i>SOV Model D and model S</i>
<b>GROUP</b>	1
<b>PURPOSE</b>	<i>Free Standing Cookers</i>
<b>CHARACTERISTICS</b>	<i>Number of ways: 2 or 1 Outlets Maximum pressure: 100 mbar Reference flow: 2,4 m<sup>3</sup>/h fully open, with air at 20 mbar and 1 mbar pressure drop Nominal diameter: 15 T<sup>a</sup> max.: 150 °C T<sup>a</sup> min.: 0 °C</i>
<b>NUMBER OF MECHANICAL CYCLES</b>	<i>10.000 cycles</i>
<b>MOUNTING POSITION</b>	<i>Appliance Inlet</i>
<b>RANGE OF PRESSURES IN MB</b>	<i>8- 100 mbar</i>
<b>CONNECTIONS</b>	<i>Inlet: Joint, Male G1/2 Outlet: Joint Female G1/2 and Biconic</i>
<b>GAS TYPE</b>	<i>1st, 2nd y 3th families</i>
<b>TORQUE OF FITTING OUTLET (max)</b>	<i>35 Nm (Taps Outlet) 12 Nm (Oven Outlet)</i>
<b>TORQUE OF FITTING INLET (max)</b>	<i>55 Nm</i>
<b>TORQUE OF 8 LATERAL HOLES (max)</b>	<i>1,4 Nm</i>
<b>TURNING OF 2 UPPER HOLES (max)</b>	<i>1.2Nm</i>

2. Instruction manual for use and maintenance intended for the user.

- Component does not require any maintenance. Washing the thermostat with soapy water or other products may involve deterioration.
- Do not pour liquids in the component.
- The appliance can only be switched on in the user's presence.
- The component must not be manipulated or repaired in any way
- In case of malfunction, the manufacturer of the appliance and its specialized technical service carries out the replacement of the component.
- The transformation of the component to use another gas will be carried out by personnel authorized by the manufacturer of the appliance
- The installer must check the suitability of the component functions for the intended use
- An inlet strainer must be fitted to prevent the ingress of foreign material (hole dimension not exceeding 1,5mm and prevent the passage of 1 mm diameter pin gauge)
- Designed lifetime for safe operation: 10 years or the maximum declared number of operations, whichever is reached first. Note: The warranty is governed by other regulations and has no connection with the "Designed lifetime for safe operation"