

EU type examination certificate
EU-Baumusterprüfbescheinigung

CE-0085CL0295

Product Identification No.
 Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Copreci S. Coop. Araba Ibilbidea, 3, E-20550 Aretxabaleta/Guipuzcoa
Distributor <i>Vertreiber</i>	Copreci S. Coop. Araba Ibilbidea, 3, E-20550 Aretxabaleta/Guipuzcoa
Product Category <i>Produktart</i>	accessories for gas appliances/pressure equipment: Functional control (4103)
Product Description <i>Produktbezeichnung</i>	Manually operated tap for gas appliances for cooking, baking, grilling
Model <i>Modell</i>	CAM 23800/...; CAM 23900/...
Countries of Destination <i>Bestimmungsländer</i>	AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK
Test Reports <i>Prüfberichte</i>	supplement test: 18/276/4104/400 from 10.09.2019 (EBI)
Test Basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 1106 (01.09.2010)

Date of Expiry / File No. 16.04.2029 / 19-0527-GER
Ablaufdatum / AZ

30.10.2019 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body
 Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EU Regulation

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EU-Verordnung EU/2016/426.




Deutsche
 Akkreditierungsstelle
 D-ZE-16028-01-01

DVGW CERT GmbH
 Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
 53123 Bonn

Tel. +49 228 91 88 - 888
 Fax +49 228 91 88 - 993

www.dvgw-cert.com
 info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
fuel gases of the 1., 2. & 3. gas family	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
CAM 23800/...; CAM 23900/...	max. operating pressure: 65 mbar	

Hints of Utilization /Remarks
Verwendungshinweise / Bemerkungen

type: CAM 23800/219:

connection: at the input side square fitting with 9,52 mm flat section with 1/4-20 UNC-2B;
at the output side double conical screw connection with union nut

type: CAM 23800/218:

with outlets for internal and external burners, in each case with variable small position

type: CAM 23900/075:

with outlets for internal and external burners, in each case with variable small position; square shaft operation

connection: at the input side flange- or clamp screw connection or biconical ring screw connection with union nut or conical male thread;

at the output side flange pipe joint or biconical ring screw connection with union nut or -screw or clip connection or metric female thread for screwing in nozzle

ambient temperature range: 0...+150 °C

group: 2

DIVISION