



Ref. Certif. No.

ES2225-M1-AENOR

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

INDUCTION GENERATOR

Name and address of the applicant

COPRECI, S.COOP.  
AV DE ÁLAVA, 3  
20550 ARETXABALETA (Gipuzkoa - Spain)

Name and address of the manufacturer

SAME AS ABOVE

Name and address of the factory

SAME AS ABOVE

Note: When more than one factory, please report on page 2

Additional Information on page 2

Ratings and principal characteristics

See Annex

Trademark (if any)

COPRECI

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

E Cook 8G 3I\*\*\*-\*\*\*; E Cook 8G 4I\*\*\*-\*\*\*

Additional information (if necessary may also be reported on page 2)

Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60335-1:2010;  
IEC 60335-1:2010/COR1:2010;  
IEC 60335-1:2010/COR2:2011;  
IEC 60335-1:2010/AMD1:2013;  
IEC 60335-1:2010/AMD1:2013/COR1:2014;  
IEC 60335-1:2010/AMD2:2016;  
IEC 60335-1:2010/AMD2:2016/COR1:2016;  
IEC 60335-2-6:2014  
IEC 60335-2-6:2014/AMD1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate

2022060351P1

This CB Test Certificate is issued by the National Certification Body

AENOR INTERNACIONAL S.A.U.  
CI Génova, 6  
ES-28004 MADRID (SPAIN)

Date: 2022-12-01

Signature:   
Rafael GARCÍA MEIRO  
Chief Executive Officer

# ANNEX TO CB CERTIFICATE N° ES2225-M1-AENOR

## CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

**PRODUCT: INDUCTION GENERATOR**

**Trade mark: COPRECI**

Reference/Technical Code	Rated Voltage	Rated input	Frequency	Protection against electrical shock
ECOOK 8G 3I***_***	220-240 V~/380-415 V3N~	3400 W; 6600 W	50/60 Hz	Class I
ECOOK 8G 4I***_***	220-240 V~/380-415 V3N~	7200 W	50/60 Hz	Class I

### Technical code definition

Information from the manufacturer. The laboratory does not bear responsibility on it.

ECOOK 8G \*I\*\*\*\_\*\*\*

#### Project designation

ECOOK 8G

#### Number of induction heaters

4I 4 Induction heaters  
3I 3 Induction heaters

#### User interface description

A STD  
B XLS  
C XLL  
D MONOSLIDER  
T TFT  
E ELC  
P PENTA  
J DUOSLIDE

#### Hob width

45 45 cm  
60 60 cm  
75 75 cm  
77 77 cm. Linear  
90 90 cm. Linear

#### Configuration hob description

A 4 Heaters standard  
B 3 Heaters standard  
E 3 Heaters 45 cm  
F 4 Heaters 75 cm PANORAMIC STANDARD  
G 3/4 Heaters 60 cm Bridge  
H 4 Heaters 75 cm Bridge  
N 3/4 Heaters with Ø240 (3000W)  
NR 4 Heaters PANORAMIC with TFT RF  
NH 3 Heaters linear with Ø240  
NHR 3 Heaters linear with RF  
o Induction module without TFT  
(\* K Power limited

Note: This code is general for different products. Not all combinations of codes are possible. See possible combinations of the 8G family in the schematics section.