



Ref. Certif. No.

ES1821-M1

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME**

CB TEST CERTIFICATE

Product

COOKING TABLE GLASS CERAMIC INDUCTION

Name and address of the applicant

COPRECI, S.COOP.
AV DE ÁLAVA, 3
20550 ARETXABALETA (Gipuzkoa – Spain)

Name and address of the manufacturer

SAME AS ABOVE

Name and address of the factory

SAME AS ABOVE

Note: When more than one factory, please report on page 2

Additional Information on page 2

Ratings and principal characteristics

220-240V~/380-415 3N~; 50/60 Hz; 5800 W; Ind 3,3 kW;
Class I

Trademark (if any)

COPRECI

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

ECOOK 7G *I*R***-**(****) (See annex)

Additional information (if necessary may also be reported on page 2)

Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60335-1:2010 incl. Corr. 1:2010 and Corr. 2:2011 + A1:2013
IEC 60335-2-6:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

2016110715P1-M1

This CB Test Certificate is issued by the National Certification Body

AENOR INTERNACIONAL S.A.U.
CI Génova, 6
ES-28004 MADRID (SPAIN)

Date: 2018-10-30


Signature: Rafael GARCÍA MEIRO
Chief Executive Officer

ANNEX TO CB CERTIFICATE N° ES1821-M1

CERTIFIED REFERENCES AND THEIR MAIN RATINGS

PRODUCT: COOKING TABLE GLASS CERAMIC INDUCTION

Technical code definition: ECOOK 7G *I*R***-**(****)

Project designation: ECOOK 7G HYBRID MODELS

Number of induction heater

| | |
|----|---------------------|
| 1I | 1 Induction heater |
| 2I | 2 Induction heaters |

Number of radiant heaters

| | |
|----|------------------|
| 1R | 1 Radiant heater |
| 2R | 2 Radiant heater |

User interface description

| | |
|---|-----|
| B | XLS |
|---|-----|

Hob width

| | |
|----|-------|
| 60 | 60 cm |
|----|-------|

Configuration hob description

| | |
|----|--|
| A | 1 Induction heater Ø 210 |
| B | 2 Induction heaters Ø 180- Ø145 |
| G | 2 Induction Ø 180- Ø 180 BRIDGE |
| AK | 1 Induction heater Ø 210 power limitation Korean market |
| BK | 2 Induction heater Ø 180- Ø 145 power limitation Korean market |
| GK | 2 Induction Ø 180- Ø180 BRIDGE power limitation Korean market |

Radiant heater description (only for 1R configuration)

| | |
|------|-----------------|
| 23OD | Ø 230mm Double |
| 25OT | Ø 250 mm Triple |