



Ref. Certif. No.

ES2559-AENOR

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

BUILT-IN GLASS INDUCTION CERAMIC HOB

Name and address of the applicant

COPRECI, S.COOP.
AV DE ÁLAVA, 3
20550 ARETXABALETA (Gipuzkoa - España)

Name and address of the manufacturer

SAME AS ABOVE

Name and address of the factory

SAME AS ABOVE

Note: When more than one factory, please report on page 2

Additional Information on page 2

Ratings and principal characteristics

220-240V~/380-415 3N~, 50/60 Hz; 5800 W; Ind 3,3 kW; Class I

Trademark (if any)

COPRECI

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

ECOOK 7G *I*R***-**(****)

Additional information (if necessary may also be reported on page 2)

Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60335-1:2010
IEC 60335-1:2010/COR1:2010
IEC 60335-1:2010/COR2:2011
IEC 60335-1:2010/AMD1:2013
IEC 60335-1:2010/AMD1:2013/COR1:2014
IEC 60335-1:2010/AMD2:2016
IEC 60335-1:2010/AMD2:2016/COR1:2016
IEC 60335-2-6:2014
IEC 60335-2-6:2014/AMD1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate

2022010033P1

This CB Test Certificate is issued by the National Certification Body

AENOR INTERNACIONAL S.A.U.
CI Génova, 6
ES-28004 MADRID (SPAIN)

Date: 2022-06-06

Signature: 
Rafael GARCÍA MEIRO
Chief Executive Officer

ANNEX TO CB CERTIFICATE N° ES2559-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Technical code definition

ECOOK 7G *|R***_** ****

Project designation

ECOOK 7G HYBRID MODELS

Number of induction heaters

1I 1 Induction heater

2I 2 Induction heaters

Number of radiant heaters

1R 1 Radiant heater

2R 2 Radiant heater

User Interface description

B XLS

Hob width

60 60 cm

Configuration hob description

A 1 Induction heater \varnothing 210

B 2 Induction heater \varnothing 180 - \varnothing 145

G 2 Induction \varnothing 180 - \varnothing 180 BRIDGE

AK 1 Induction heater \varnothing 210 power limitation Korean market

BK 2 Induction heater \varnothing 180 - \varnothing 145 power limitation Korean market

GK 2 Induction \varnothing 180 - \varnothing 180 BRIDGE power limitation Korean market

Radiant heater description (only for 1R configuration)

230D \varnothing 230 mm Double

250T \varnothing 250 mm Triple